MPAGE4

PAGING STATIONS Desktop Paging Station



PRODUCT OVERVIEW

MPAGE4 is a 4-zone desktop paging station compatible with the MIMO54, DAM614, CA series, etc. It allows for real-time paging with zones' destination in selection.

KEY FEATURES

- 4 zone selection keys
- SELECT ALL, and PAGE keys
- Selectable chime melody
- Gooseneck microphone

APPLICATIONS

• Paging, voice messages and speech



MECHANICAL DIAGRAMS





TECHNICAL DATA

| Microphone type | Non-removable gooseneck condenser microphone |
|----------------------------------|---|
| Polar pattern | Cardioid |
| Microphone frequency response | 50Hz - 18KHz (-10dB) |
| Output level | 0dBV @ 104dB SPL ±7dB (internal adj.) |
| Chime | DIP selector for mode 1, 2 or 3 or none |
| Maximum audio cable length | Twisted pair 20m, Shielded 80m (provided that minimum voltage is assured) |
| Number of paging zones | 4 |
| Indicators | Selection LED on all keys |
| Power supply | +6 to 15V |
| Connector | RJ45 |
| Maximum power consumption | 40mA |
| Dimensions (microphone excluded) | W 120mm x D 126mm x H 43mm |
| Weight | 625 g |
| Included accessories | Windscreen |
| | |

All product characteristics are subject to variation due to production tolerances. NEEC AUDIO BARCELONA S.L. reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications. Motors, 166-168 08038 Barcelona - Spain - (+34) 932238403 information@ecler.es **www.ecler.com**